

PARVUE[®]

Innovative, Durable & Functional



ParVue's wrap around glazing provides 360° visibility, maximizing light and resulting in an "open" interior..



PARVUE[®]

The ParVue[®] Series represents one of Par-Kut's most innovative designs. Featuring corner to corner glass, the ParVue[®] allows 360° visibility - essential for security. Wrap around glazing is an attractive addition to the ParVue[®] design making the exterior easily customized and a popular choice for architectural applications.

Single or double roof fascia applications conceal rooftop utilities while also enhancing the clean ParVue[®] design. As with all Par-Kut steel buildings, the ParVue[®] boasts low-maintenance materials and quality construction making it the most durable and long lasting booth available. See the complete options list on the enclosed insert.

SPECIFICATIONS

- 2.1** Short form specification: Pre-assembled booth unit(s) shall be Model _____ PARVUE[®] (Model is determined by length first then width. i.e. 6' x 8' booth is model 86 PARVUE[®]) as manufactured by Par-Kut International, Inc. *Note: Minimum PARVUE[®] size available is 3' x 6'.
- 2.2** Structure: Prefabricated steel building shall be single unit welded steel construction with 14-gauge galvanized steel panels and tubing on the exterior and 18-gauge galvanized steel interior panels. Building to be shipped completely assembled. All welded joints ground smooth. Aluminum or fiberglass construction not acceptable.
- 2.3** Base and floor: Base height shall be 4 inches for outside use. Floor shall be 12-gauge galvanized steel, 4-way tread plate. Four 1/4" steel angle iron anchor clips with pre-drilled holes are provided to secure building. Anchors provided by installer shall be galvanized or stainless steel.
- 2.4** Door(s) shall be top-suspended heavy duty sliding galvanized steel, 18-gauge minimum, fully weather-stripped. Include Adams Riter #1850 hook bolt type lock, view window and all roller assembly hardware. Trolleys shall be ball bearing, adjustable pendant type.
- 2.5** Windows: Shall be steel construction properly primed and finish painted. All windows shall be fixed unless clearly stated otherwise. Windows will have interior anodized aluminum stops screwed in place for easy glass replacement, if required. Furnish glass of type specified herein. Windows shall be squared and weather-sealed at the factory. If sliding windows are required, provide sliding windows as shown on drawings for ventilation and/or transaction purposes.
- 2.6** Glazing: All windows and doors shall contain clear tempered safety glass, 1/4" minimum thickness.
- 2.7** Finish: All steel surfaces shall be painted with rust inhibitive epoxy primer. All exposed interior and exterior steel surfaces shall be painted with one finish coat of industrial acrylic epoxy. Choice of single color of paint as selected by owner from manufacturer's standards.
- 2.8** Canopy: Shall be 14-gauge minimum galvanized steel and standard overhang shall extend 6" beyond the walls. For buildings wider than 7 feet 6 inches, the standard overhang shall extend 3" beyond the walls. Standard fascia height shall be 12".
- 2.9** Roof: Provide lifting ring(s) welded in roof for onsite lifting of unit. Roof surface shall be 14-gauge galvanized steel sheet. Roof seams shall be continuously welded, caulked and weatherproofed. Roof shall drain to downspout(s).
- 2.10** Insulation: Walls shall be insulated with 2" rigid fiberglass board, R=10. Roof structure fully insulated, R=17.4.
- 2.11** Work counter: One 22" minimum depth 14-gauge painted steel counter across width of booth mounted 32" above floor. Include one 16" wide steel storage drawer. Counter shall be welded in place. Include one electrical cord access hole install in counter above receptacle.
- 2.12** Electrical: Unit shall be delivered complete with all wiring required for two-lamp recessed shielded fluorescent light with lamps and wall switch, one 110V duplex outlet, heater, a 100A 12-circuit load center with branch circuit breakers and 100A main breaker. All wiring copper No. 12 minimum, enclosed in EMT. All fittings, wiring devices and fixtures UL listed. Ready for site connection. Three wire 240/120V single-phase service required.
- 2.13** Heater: Electrical wall heater shall be fan-forced type including integral thermostat. Minimum heater size shall be 120V/1500W. (Specify optional 208/240V units for larger buildings and cold climates.)
- 2.14** Optional features: Provide items available from manufacturer's optional equipment list at direction of owner/architect to best meet site requirements.



I N T E R N A T I O N A L

40961 Production Drive Harrison Twp., Michigan 48045-3443

PHONE (586) 468-2947 FAX (586) 463-6059

1-800-394-6599

website: www.parkut.com